

# EU Type Examination Certificate

Date: 2020/07/10

n. **084202802/OE**

Validity:  
2025/07/09

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II).

Manufacturer: (Responsible of the PPE)	<b>ALPINESTARS SpA</b> Viale E. Fermi, 5 – 31031 ASOLO (TV) – ITALIA
Type of PPE:	<b>motorcyclists' protective footwear</b>
Category of PPE:	<b>II</b> : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.
Model:	<b>"KTM J-6 AIR 0254121"</b> col. ORANGE/BLACK (41)
Description:	<p><b>ORANGE/BLACK (41)</b></p>  <p><u>fastening system</u>: by means of laces; <u>processing</u>: Ago; <u>outsole</u>: in black and fluorescent orange "RUBBER 65+3 SHA" (AL-19); <u>upper</u>: - black suede leather along the feather line area and in the eyelet area (PY-143); - black leather coated with black material "1.4-1.6MM H.P. ECO TECH COMFORT LEATHER" (PY-142), black felt "1.0 MM NIK NON-WOVEN" (PY-500) and black fabric "NYLON 210D" (PY-533) coupled together; - perforated ice coloured leather coated with fluorescent orange polymeric material "1.4-1.6MM H.P. ECO TECH COMFORT LEATHER + PERFORATION" (PY-142P) coupled with beige fabric "0.6MM TWILL REINFORCEMENT + SA" (PY-555); <u>rear joint</u>: fluorescent orange knit fabric "MESH KN 0941" (PY-233), light blue/white foam "6.0 MM F5090 FOAM" (PY- 419), black knit fabric inward side coated with black polymeric material "0.5MM DL 805 EMB:P000 FMG" (PY-230), light blue/white foam "4.0 MM KHT FOAM" (PY-402) and light blue/white foam "4.0 MM F5090 FOAM" (PY-418) coupled together; <u>vamp and rear/quarter lining</u>: black three-dimensional fabric "CHA 1350 AIR MESH" (PY-357); <u>collar lining</u>: black knit fabric coated with black material "0.7MM WL 707 EMB:P023 FWA" (PY-285-1); <u>higher tongue lining</u>: black knit fabric coated with black material "0.7MM WL 707 EMB:P023 FWA" (PY-285-1); <u>eyelet area lining</u>: black knit fabric coated with black material "0.7 MM KUJJU WATER REPELLENT" (PY-266); <u>tongue</u>: - black knit fabric "MESH KN 0941" (PY-233) coupled with white foam "6.0 MM KHT FOAM WHITE" (PY-401), in the lower area; - perforated black coated leather "1.4-1.6MM H.P. ECO TECH COMFORT LEATHER" (PY-142) coupled with white foam "6.0 MM KHT FOAM WHITE" (PY-401), in the higher area; <u>insole</u>: semi-rigid cellulosic material "TEXON T70 2.9-3.1MM" (PY-694) matched with white felt "1.0 MM NON-WOVEN(NIK-10)" (PY-500) in contact with the removable insock; <u>removable insock (perforated)</u>: grey foam matched with black knit fabric marked "READY TO RACE" in white color, in the heel area (AL-20).</p> <p>The shoe has the following stiff inserts in polymeric material inserted in the upper: - <u>internal and external ankle insert</u>: black and white disc.</p>

Technical Standard:	<b>EN 13634:2017</b>	Protective footwear for motorcycle riders – Requirements and test methods.
---------------------	----------------------	--

## EU Type Examination Certificate

Date: 2020/07/10

n. **084202802/OE**

Validity:  
2025/07/09

Intended use:	use by motorcyclists for normal road activity, mainly on urban roads.								
Size range:	from US 6 to US 14								
Technical File:	<b>DC-12087/E</b>								
Test report:	<b>RCT n° 3912104/E</b>								
Functions and performance levels:	<p><b>Requirements according to EN 13634:2017:</b> all mandatory ones, among which:</p> <table border="0"> <tr> <td>Height of upper</td> <td>level 1</td> </tr> <tr> <td>Impact abrasion resistance of the upper</td> <td>level 1</td> </tr> <tr> <td>Impact cut resistance of the upper</td> <td>level 2</td> </tr> <tr> <td>Transverse rigidity of the whole footwear</td> <td>level 2</td> </tr> </table> <p>NOTE: The Technical Standard provides 2 performance levels with level 2 meaning the higher performance.</p>	Height of upper	level 1	Impact abrasion resistance of the upper	level 1	Impact cut resistance of the upper	level 2	Transverse rigidity of the whole footwear	level 2
Height of upper	level 1								
Impact abrasion resistance of the upper	level 1								
Impact cut resistance of the upper	level 2								
Transverse rigidity of the whole footwear	level 2								

Marking: printed on stitched labels showing the following information:



- **CE Marking:**
- Name/Trademark of the Manufacturer + complete address (on a different label);
- pictogram indicating motorcycling use + nr / year of the Standard of reference + levels of performance reached during laboratory tests + optional requirements symbols (WR + WAD);
- the "i in the booklet" pictogram inviting the user to read the User Manual;
- designation of the footwear (alphanumeric code: unique/unambiguous);
- size of the footwear (US + EUR);
- additional information: "Made in...", "Designed and developed in...", internal codes, date of production (month - year, on a different label).



Viale Enrico Fermi, 5  
Asolo TV 31011 Italy

POxxxxx - M12 - 2019



NOTE: The Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

